

SK-ADSL990ER/EB



Description:

The SK-DSL990ER/EB 2+ Router/Modem provides Full rate (ANSI and G.DMT) as well as G.lite ADSL standards line support, and can be connected to PC through Ethernet. This product supports bridge feature set for the integration of ADSL service into corporate or home LAN and WAN.

Features

- Downstream up to 24Mbps, Upstream up to 1Mbps, upgradable to ADSL 2/2+
- Strong routing functions
- Support up to 8 PVC settings
- Friendly English configuration interface
- Support diagnose functions
- Built-in PPPoE function(only ER)
- Connecting to ISP automatic , especially adapt to LAN
- Support remote upgrade, and remote management
- Support Multicast function
- Totally compatible with the main DSLAMS
- Build-in watch software, inspect network status real time

Specifications

Products	Router/Modem
LAN Specification	IEEE 802.3, 802.1d
WAN Specification	ANSI T1.413 ISSUE2, ITU G.992.1(G.DMT), ITU G.992.2(G.Lite), ITU-T G.992.1(G.DMT), ADSL2/2+(ITU-T G. 992.3, ITU-T G.992.5), IEEE802.3, IEEE802.3u;
Power Adaptor	AC Power : 9V/ 800mA
Dimension (L *W * H)	168*112*32 (mm)
Weight	250g (Modem only)
Operating ambient temperature	0°C ~ 40°C with airflow
Storage ambient temperature	-10°C ~ 85°C
Operating Humidity	10% to 90% non-condensing
Non-operating storage humidity	5% to 95% non-condensing
Connector	Two RJ11 Jack (pins 2 or 4, tip and ring)
Cerification	CE