



802.11b/g/n 2T2R Wireless LAN USB Adapter

Mini-size design, Extend range, High data transfer rate

SK-7718Un



Features :

- Complies with 802.11n draft, 802.11g and 802.11b standards.
- Farther coverage, less dead spaces and higher throughput with MMO technology.
- Supports QoS-WMM, WMM-PS.
- Supports 64/128-bit WEP, WPA (TKIP with IEEE 802.1x), WPA2 (AES with IEEE 802.1x) functions for high level of security.
- Supports the most popular operating system: Windows 2000/XP/XP64/Windows Vista.
- Supports USB 2.0/1.1 interface.
- Supports WPS (WiFi Protected Setup).
- Portable and mini-size design.

Specification :

| | |
|------------------|---|
| Product | 802.11b/g/n 2T2R Wireless LAN USB Adapter |
| Chipset Solution | Ralink RT2870+RT2820 |
| Standard | IEEE 802.11b/g/n |
| Bus Type | USB 2.0 Type A |
| Frequency Band | 2.4000~2.4835GHz (Industrial Scientific Medical Band) |
| Data Rate | 11b: 1/2/5.5/11Mbps 11g: 6/9/12/24/36/48/54Mbps 11n (20MHz): MCS0-15, 32 with Half Guard Interval Support (up to 72/144Mbps) 11n (40MHz): MCS0-15, 32 with Half Guard Interval Support (up to 150/300Mbps) |
| Security | WEP 64/128, WPA, WPA2 Cisco CCX Support |
| Antenna | Internal 2 Antennas |
| Drivers | Windows 2000/XP/XP64/Windows Vista |
| LEDs | Link/Activity |
| Dimension | (TBC) |
| Temperature | 32~131°F (0 ~55°C) |
| Humidity | Max. 95% (NonCondensing) |
| Certification | FCC , CE |