



802.11b/g/n 2T3R Wireless LAN PCI Card

Extend range, High data transfer rate



SK-7728

Features :

- Comply with 802.11n draft, 802.11g and 802.11b standards.
- Farther coverage, less dead spaces and higher throughput with MMO technology.
- Supports QoS-WMM, WMM - PS.
- Supports 64/128-bit WEP, WPA (TKIP with IEEE 802.1x), WPA2 (AES with IEEE 802.1x) functions for high level of security.
- Supports the most popular operating system: Windows 2000/XP/XP64/Windows Vista.
- Supports 32-bit PCI interface.
- Supports WPS (WiFi Protected Setup).

Specification :

Product	802.11b/g/n 2T3R MIMO Wireless LAN PCI Card
Chipset Solution	Ralink RT2860+RT2820
Standard	IEEE 802.11b/g/n
Bus Type	32-bit PCI
Frequency Band	2.4000~2.4835GHz (Industrial Scientific Medical Band)
Data Rate	11b: 1/2/5.5/11Mbps 11g: 6/9/12/24/36/48/54Mbps 11n (20MHz): MCS0-15, 32 with Half Guard Interval Support (up to 144Mbps) 11n (40MHz): MCS0-15, 32 with Half Guard Interval Support (up to 300Mbps)
Security	WEP 64/128, WPA, WPA2 Cisco CCX Support
Antenna	External 3 Antennas with Two TX and Three RX (Connector: RP-SMA)
Drivers	Windows 2000/XP/XP64/Windows Vista
LEDs	Link, TX/RX
Dimension	(TBC)
Temperature	32~131°F (0 ~55°C)
Humidity	Max. 95% (NonCondensing)
Certification	FCC , CE